

RECESSED ACCESS DOOR FOR EXTERIOR CEILINGS

GFRC-R

GLASS FIBER REINFORCED CEMENT RADIUS CORNER

Application

Glass fiber reinforced cement, ceiling access doors are designed to blend seamlessly into exterior soffits/ceilings

Product Features

- Portland Cement, Fiber, Post Consumer Recycled Glass
- Tapered edge for joint tape
- Easily textured
- Lightweight
- No cracking or shrinkage
- Mold and moisture resistant

GFRC-R ACCESS DOOR SPECIFICATIONS:

- Shell Thickness = .125" .375"
- Fastener Test Pull Out (wood stud) = 525 lb. avg.
- Fastener Test Pull Out (metal stud) = 525 lb. avg.
- Fastener Push Through Test = 350 lb. avg.
- Fuel Contribution (ASTM-E84-80) = 0
- Flame Spread (ASTM-E84-80) = 0
- Smoke Index (ASTM-E84-80) = 0
- Combustion (ASTM-E84-80) = 0

GFRC-R STANDARD SIZES

(Special sizes available upon request)

| Door Size | Ceiling Opening | Weight |
|---------------------|---------------------|-------------|
| Inches (mm) | Inches (mm) | LBS (kg) |
| 9 x 9 (229 x 229) | 15 x 15 (381 x 381) | 6.0 (2.73) |
| 12 x 12 (305 x 305) | 18 x 18 (457 x 457) | 9.0 (4.09) |
| 16 x 16 (406 x 406) | 22 x 22 (559 x 559) | 10.0 (4.53) |
| 18 x 18 (457 x 457) | 24 x 24 (610 x 610) | 11.0 (5.0) |
| 24 x 24 (610 x 610) | 30 x 30 (762 x 762) | 16.0 (7.27) |

For detailed specifications see submittal sheet

