

HDSS-6020

Self Stick Duct Doors, *for Sheet Metal Duct*

Application

- Provides easy access to sheet metal ducts

Product Features

- Innovative self stick frame for easy installation
- Insulated door panel, single cam, hinged
- Tested to 10" SP with minimal leakage

Options:

- ALUMINUM
- STAINLESS STEEL
- CYLINDER LOCK & KEY
- HASP + STAPLE
- L HANDLE

HDSS-6020 Duct Access Door Specifications:

Door: 24 gauge galvanized steel, double panel

Frame: 24 gauge galvanized steel

Hinge: Continuous aluminum piano hinge

Insulation: Door panel filled with 1" fiberglass insulation

Gasketing: 1/8" thick by 1/2" wide closed cell neoprene gasketing between door and frame. 1/8" thick by 1 1/2" wide adhesive bonded gasket between frame to duct

Latch: Self tightening, hand operated cam latches

Hardware: Hex head sheet metal screws



STANDARD SIZES *(other sizes available upon request)*

Nominal Door Size W&H

Weight per Door

Inches	mm	Duct Opening	Latches	lbs.	kg.
6 X 6	150 X 150	4.5 X 4.5	1	1.25	0.6
8 X 8	200 X 200	6.5 X 6.5	1	1.75	0.8
10 X 10	250 X 250	8.5 X 8.5	1	2.75	1.3
12 X 12	300 X 300	10.5 X 10.5	1	3.75	1.7
12 X 18	300 X 450	10.5 X 16.5	2	3.5	1.6
14 X 14	350 X 350	12.5 X 12.5	2	4.75	2.2
16 X 16	400 X 400	14.5 X 14.5	2	5.25	2.4
18 X 18	450 X 450	16.5 X 16.5	2	6.75	3.1
20 X 20	500 X 500	18.5 X 18.5	2	9	4.1
24 X 24	610 X 610	22.5 X 22.5	2	12	5.5

