

# FWC-5015

Fire Rated Access Door,  
*Recessed for Drywall Ceilings*

**Application**

- For installation in drywall ceilings requiring concealing of the door panel consistent to surroundings
- For use in ceilings, fire-rated for up to 90-minutes with a temperature rise of max 250° F over 30 minutes

**Product Features**

- Recessed reinforced insulated door fitted with 5/8" Fire-rated drywall.
- Concealed hinge & self-centering device ensures seamless appearance in ceiling
- Self-closing & self-latching door mechanism
- Perforated Frame ensures trouble-free application of skim coat to edge of the door
- Zinc coated steel provides superior corrosion resistance
- Testing Standards: ASTM E119-16/CAN ULC S101 & NFPA 251.



PATENT PENDING

**FWC-5015 Access Door Specifications:**

Door: Steel-22 Gauge recessed fitted with 5/8" thick drywall suitable to accept skim coat finish on site.

Door Frame: Steel-22 Gauge press bent for strength and rigidity with pre-punched flanges for convenient mounting and accepting skim coat finish on site

Hinge: Concealed

Fire Rating (Ceilings): Fire rated for 90 mins with a temperature rise of max 250°F over 30 mins in accordance with ASTM E119-16/CAN ULC S101 & NFPA 251, for a max size of 24"x36"

Latch: Self-latching bolt, operated by flush key

Finish: Satin coat steel

**FWC-5015 STANDARD SIZES**

*(other sizes available upon request)*

Nominal Door Size W&H		Latches	Weight per Door	
Inches	mm		lbs.	kg.
12 X 12	305 X 305	1	10	4.5
16 x 16	406 X 406	1	14	6.4
18 X 18	457 x 457	1	18	8.2
24 X 24	610 x 610	1	29	13.1
24 X 36	610 X 914	2	42	19.0

Ceiling opening is W + 3/8" ( 9 mm)

For detailed specifications see submittal sheet

PATENT PENDING

