

PA-3000

FLUSH NON-RATED - *Plastic Access Door*

Application

- Easy access to walls and ceilings
- Economical and attractive

Product Features

- High impact styrene plastic with U.V. stabilizers
- Hinged with a removable feature

PA-3000 Access Door Specifications:

Door / Door Frame: 1/8" high impact styrene plastic with U.V. stabilizers
 Flush to frame — rounded safety corners, one piece outside flange with 3/4" deep mounting frame

Standard Latch: Snap latches allow door to fit tightly within frame

Door Hinge: Concealed

Finish: White, with textured exposed surfaces

PA-3000 STANDARD SIZES

Nominal Door Size W&H		Weight per Door	
inches	mm	lbs.	kg.
4 X 6	101 X 152	.5	.25
6 X 9	152 X 228	.5	.25
8 X 8	203 X 203	.5	.25
12 X 12	305 X 305	.5	.25
14 X 14	356 X 356	.75	.33
14 X 29	358 X 735	4	1.87
18 X 18	457 X 457	2.25	1
22 X 22	560 X 560	4	1.87
24 x 24	610 x 610	4.75	2.15

Wall or ceiling opening is $W + 3/8"$ (9 mm)
 For detailed specifications see submittal sheet



PA-3000 View of door back

