

DW-5015

RECESSED ACCESS DOOR

Application

- For installation in drywall surfaces when it is required to conceal the door panel

Product Features

- Recessed 5/8" to receive drywall
- Door flange is a textured galvanized steel taping bead with pre-punched holes

DW-5015 Access Door Specifications:

Material: Steel Door 22 gauge,

Mounting Frame: 22 gauge

Door: Recessed 5/8"

Door Frame: Galvanized steel drywall taping bead on all sides

Hinge: Concealed.

Standard Latch: Slotted Screwdriver Cam Latch

Optional Latches/Locks: Cylinder lock and key, allen head cam latch, spanner head cam latch, torx head with security pin

Finish: Satin coat steel



**DRYWALL
NOT INCLUDED**

DW-5015 STANDARD SIZES

(other sizes available upon request)

Nominal Door Size W&H		Latches	Weight per Door	
Inches	mm		lbs.	kg.
8 X 8	203 X 203	1	2.65	1.2
12 X 12	305 X 305	1	3.45	1.5
18 X 18	457 X 457	1	6.65	3.0
24 X 24	610 X 610	1	10.40	4.7
24 X 36	610 X 914	2	16.35	7.4

Wall or ceiling opening is $W + 3/8"$ (9 mm)
For detailed specifications see submittal sheet

