

DW-5040

Flush Access Door, *for Drywall*

Application

- Designed specifically for installation in drywall walls and ceilings **after** drywall has been installed

Product Features

- Formed door panel with flanges on four sides
- Unique concealed hinge, door flange is a perforated tapping bead with pre-punched holes

DW-5040 Access Door Specifications:

Material: 20 gauge galvanized formed door panel, 26 gauge galvanized frame

Door: Formed door panel with multiple bends for added strength, flanged on four sides, Integral perforated tapping bead adds rigidity

Hinge: Concealed

Standard Latch: Slot screwdriver operated cam latch

Optional Latches/Locks: Cylinder lock & key; allen head cam latch; spanner head cam latch, torx

Finish: 5 stage iron phosphate preparation with white baked-on polyester powder coat on door panel. Frame to be mill finish



STANDARD SIZES *(other sizes available upon request)*

Nominal Door Size W&H		Latches	Weight per Door	
inches	mm		lbs.	kg.
6 X 6	152 X 152	1	1.5	.68
8 X 8	203 X 203	1	2.0	.91
10 X 10	254 X 254	1	2.5	1.14
12 X 12	305 X 305	1	3.0	1.36
14 X 14	355 X 355	1	5.0	2.27
16 X 16	406 X 406	1	5.5	2.5
18 X 18	457 X 457	1	6.0	2.73
22 X 22	560 X 560	1	8.0	3.64
24 X 24	610 X 610	1	9.0	4.09
24 X 36	610 X 914	1	13.0	5.91
30 X 30	762 X 762	2	15.0	6.82
36 X 36	914 X 914	2	21.0	9.55

Wall or ceiling opening is W + 3/8" (9 mm)

For detailed specifications see submittal sheet

