

HD-5070-F

DUCT DOORS for Ductboard/Fiberglass ducts

Application

- Economical access to fiberglass ducts

Product Features

- These doors are for use in low to medium pressure fiberglass ducts
- Hinged door panel

Options:

- Aluminum, stainless steel

HD-5070F "Hinged" Fiberglass Doors Specifications:

Material: Galvanized steel

Door: 24 gauge


Mounting Frame: 24 gauge

Gasketing: 1/8" thick by 1/2" wide closed cell neoprene gasketing between door and frame and also between frame and duct.

Insulation: 1" Micro-AIRC M/F TYPE-475 R value 7.7

Hinge: Continuous aluminum piano hinge

Latch: Self tightening, hand operated cam latch



HD-5070-F STANDARD SIZES

(other sizes available upon request)

Nominal Door Size W&H		Latches	Weight per Door	
Inches	mm		lbs.	kg.
6 x 6	150 x 150	1	1.0	0.5
8 x 8	200 x 200	1	1.25	0.6
10 x 10	250 x 250	1	2.0	0.9
12 x 12	300 x 300	1	2.5	1.1
14 x 14	350 x 350	2	3.25	1.5
16 x 16	400 x 400	2	4.0	1.8
18 x 18	450 x 450	2	5.5	2.5
24 x 24	610 x 610	2	12.0	5.5

Duct opening is same size as normal door opening
For detailed specifications see submittal sheet

