



DIRECTION OF EXIT →

- NOTES:
- 1- MATERIAL: ALUMINUM
 - 2- LOADING: 300 LBS. PER SQ. FT.
 - 3- STAINLESS STEEL 316 HARDWARE
 - 4- COVERS NOT SUBJECT TO VEHICULAR TRAFFIC LOADING (SIDEWALKS AND PARKWAYS, EXCLUDING DRIVEWAYS)
 - 5- ENCLOSED SPRING LIFTING MECHANISM FOR MAX. 30 LBS. OPENING FORCE
 - 6- AREA OF FRAME IN CONTACT WITH CONCRETE TO BE PAINTED WITH BITUMINOUS COATING
 - 7- FRAME SPLIT IN 2 SECTIONS FOR SHIPPING & BOLTED TOGETHER IN THE FIELD BY OTHERS

EEH - EMERGENCY EGRESS HATCH

INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M BREAK ALL SHARP CORNERS & EDGES TO 0.01 DIMENSIONS UNLESS OTHERWISE SPECIFIED INCHES = ± 1/16 1/16 = ± 1/32 1/32 = ± 1/64		U.S.A. info@acudor.com / 800.722.0591 CANADA info@acudor.ca / 844.238.3071 INTERNATIONAL info@acudorint.com / 905.428.2240	
ALL DIMENSIONS UNLESS OTHERWISE SPECIFIED DRAWN BY: DAV CHECKED BY: DAV	SCALE: 1" = 12"	SHEET: 1 of 1	DATE: 5/6/19
PROJECT NO: 1000125971		REV: D 0	

THIS DOCUMENT IS THE PROPERTY OF ACUDOR PRODUCTS, INC. AND CONTAINS PROPRIETARY INFORMATION. IF SHOWN, NOT BE REPRODUCED, COPIED, REPRODUCED OR DISTRIBUTED (IN WHOLE OR IN PART) WITHOUT PROPER AUTHORIZATION OF ACUDOR PRODUCTS, INC.