

# FA-H20

## FLOOR DOOR H20 loading

### Application

- Designed for interior and exterior applications where watertightness is not required

### Product Features

- Angle frame construction with integral anchor flange is designed to be cast into concrete
- Diamond plate door panel is equipped with a flush aluminum drop handle and an automatic hold open arm, along with stainless steel compression spring & stainless steel slamlock
- Designed for off-street locations that may occasionally receive AASHTO H-20-44 wheel loads



Double Leaf

### FA-H20 Floor Door Specifications:

**Material:** Aluminum door and frame; stainless steel hinges and hardware

**Door:** 1/4" aluminum diamond plate reinforced to meet AASHTO specification H20-44 for traffic loading (16000 lb. wheel load with 30% added for impact)

**Hinge:** Stainless steel butt hinges with tamperproof stainless steel bolts and nuts

**Frame:** Angle frame fabricated from aluminum extrusion with an integral 1" anchor flange

**Opening Device:** Automatic hold open arm with red vinyl grip allows door panel to open to 90 degrees, locking door in open position, and allowing for easy control when closing door panel. Stainless steel compression springs provide lift assistance.

**Standard Latch:** Flush aluminum drop handle, stainless steel slamlock with a fixed inside handle, removable outside handle, and removable threaded plug

**Finish:** Mill finish, with bituminous coating applied to exterior of frame

### FA-H20 STANDARD SIZES

(other sizes available upon request)

Nominal Door Size W&H		Weight per Door	
inches	mm	lbs.	kg.
24 x 24	610 x 610	55	25
24 x 30	610 x 762	65	29.5
24 x 36	610 x 914	75	34
30 x 30	762 x 762	80	36.4
30 x 48	762 x 1220	125	56.8
36 x 36	914 x 914	110	49.9
36 x 48	914 x 1220	150	68.1
42 x 42	1067 x 1067	170	77.2
48 x 48*	1220 x 1220	200	90.8
48 x 72*	1220 x 1829	295	133.9
60 x 60*	1524 x 1524	330	149.8

\*Double Leaf

For detailed specifications see submittal sheet

