

UF-5500

UNIVERSAL FLUSH

Application

- Installation in Drywall, Plaster, Masonry, Tile or any flush surface

Product Features

- Drawn flanged door panel with rounded corners
- Concealed hinge and welds
- Galvanized steel material with white baked on polyester powder coat

UF-5500 Access Door Specifications:

Material: 12" x 12" and smaller are 20 gauge galvanized steel door & frame.

Over 15" x 15" and larger are 18 gauge galvanized steel door & frame

Door: Flush To Frame- Drawn flanged door panel with rounded corners

Door Frame: Drawn one piece trim flange and mounting frame

Hinge: Concealed

Standard Latch: Slot Screwdriver operated cam latch

Optional Latches/Locks: Cylinder lock and key; allen spanner or torx head cam latch

Finish: White baked on polyester powder coat



UF-5500 STANDARD SIZES

Nominal Door Size W&H		Latches	Weight per Door	
Inches	mm		lbs.	kg.
6 x 6	152 x 152	1	1.5	.68
8 x 8	203 x 203	1	2.0	.91
12 x 12	305 x 305	1	2.5	1.14
15 x 15	381 x 381	1	5.5	2.5
18 x 18	457 x 457	1	7.5	3.41
24 x 24	610 x 610	2	12.0	5.45

Wall or ceiling opening is $W + 3/8"$ (9 mm)

For detailed specifications see submittal sheet

