

AT-5020

SPECIALTY DOORS Recessed Access Door

Application

- For flush installation in walls or ceilings when it is required to conceal the door panel

Product Features

- Door is recessed 1"

AT-5020 Access Door Specifications:

Material: Steel

Door: 16 gauge, Recessed 1"

Mounting Frame: 14 gauge

Hinge: Concealed, pivoting rod type, for wall applications over 24"x24" we supply a concealed pin hinge

Standard Latch: Flush to surface, screwdriver operated cam latch

Optional Latches/Locks: Cylinder lock and key, allen head cam latch, spanner head cam latch

Finish: Steel: 5-stage iron phosphate preparation with prime coat of White alkyd baked-on enamel



AT-5020 STANDARD SIZES

(other sizes available upon request)

Nominal Door Size W&H		Latches	Weight per Door	
Inches	mm		lbs.	kg.
12 X 12	305 X 305	1	7	3.2
18 X 18	457 X 457	2	13	5.9
24 X 24	610 X 610	2	21	9.5
24 X 36	610 x 914	2	30	13.8

Wall opening is W + 3/8" (9 mm)

For detailed specifications see submittal sheet

Wall or ceiling opening is nominal door size + 3/8" (9 mm)

For detailed specifications see submittal sheet

