

# ASVB

## VALVE BOXES Surface Mount

### Application

- Provides easy access to valves and controls that extend outside of the finished wall, needing protection by an enclosed box.

### Product Features

- The depth of the valve box can be modified to meet all the valve and control requirements.
- When required, vision panels, louvers, engraved plates can be supplied, along with special holes for pipes or conduits.

### ASVB Valve Box Specifications:

**Material:** Stainless Steel or Steel: door & box

**Door:** 16 gauge, overlaps box, providing for a tight secure fit

**Box:** 16 gauge, fully enclosed, completely attached to frame.

When required box can be made with open back.

**Hinge:** Continuous, exposed piano hinge

**Standard Latch:** Cylinder lock & key. Also available: screwdriver operated cam latch, allen head cam latch, spanner head cam latch, flush paddle handle, thumb turn latch

**Finish:** Stainless Steel: #4 satin polish. Steel: 5 stage iron phosphate preparation with prime coat of White alkyd baking enamel

### ASVB STANDARD SIZES

(other sizes available upon request)

Nominal Door Size W&H		Opening	Weight per Door	
Inches	mm		lbs.	kg.
8 x 8 x 4	203 x 203 x 102	1	5	2.3
8 x 8 x 6	203 x 203 x 152	1	7	3.2
8 x 8 x 8	203 x 203 x 203	1	9	4.1
12 x 12 x 4	305 x 305 x 102	1	9	4.1
12 x 12 x 6	305 x 305 x 152	1	12	5.5
12 x 12 x 8	305 x 305 x 203	1	14	6.4

Wall opening is  $W + 3/8"$  (9 mm)

For detailed specifications see submittal sheet

