

FB-5060-TD

Fire Rated Uninsulated Recessed for Tile Walls

Application

- Designed for use in tiled walls
- Used whenever it is necessary to provide access in fire rated walls, when temperature rise **is not** a factor

Product Features

- Recessed 1/2" and is lined with self-furring lath
- Designed to maintain continuity in a 2-hour fire barrier wall

FB-5060-TD Access Door Specifications:

Material: Steel

Door: 16 gauge with reinforced edges, door pane recessed 1/2" and lined with self-furring lath.

Mounting Frame: 16 gauge steel

Hinge: Continuous exposed piano hinge

Fire Rating (Walls): UL — 1-1/2 hour "B" label. ULC — 2 hour "B" label. (optional) Max size 36 x 48

Standard Latch: Universal self-latching bolt, operated by a flush key. When master keying is required, doors can be prepared for rim or mortise cylinder locks.

Finish: Steel: 5 stage iron phosphate preparation with prime coat of White alkyd baked-on enamel



FB-5060-TD STANDARD SIZES

(other sizes available upon request)

Nominal Door Size W&H		Latches	Weight per Door	
Inches	mm		lbs.	kg.
12 X 12	305 X 305	1	9.0	4.1
16 X 16	406 X 406	1	13.0	5.9
18 X 18	457 X 457	1	15.0	6.8
24 X 24	610 X 610	1	24.0	10.9
24 X 36	610 X 914	2	33.0	15.0

Wall opening is nominal door size + 3/8" (9 mm)
For detailed specifications see submittal sheet

