

UF-5500

UNIVERSAL FLUSH

Application

- Installation in Drywall, Plaster, Masonry, Tile or any flush surface

Product Features

- Drawn flanged door panel with rounded corners
- Concealed hinge and welds
- Galvanized steel material with white baked on polyester powder coat

UF-5500 Access Door Specifications:

Material: 12" x 12" and smaller are 20 gauge galvanized steel door & frame.

Over 15" x 15" and larger are 18 gauge galvanized steel door & frame

Door: Flush To Frame- Drawn flanged door panel with rounded corners

Door Frame: Drawn one piece trim flange and mounting frame

Hinge: Concealed

Standard Latch: Slotted Screwdriver Cam Latch

Optional Latches/Locks: Cylinder lock and key; allen spanner or torx head cam latch, torx head with security pin

Finish: White baked on polyester powder coat



UF-5500 STANDARD SIZES

Nominal Door Size W&H		Latches	Weight per Door	
Inches	mm		lbs.	kg.
6 X 6	152 X 152	1	1.3	0.59
8 X 8	203 X 203	1	1.8	0.82
12 X 12	305 X 305	1	3.3	1.50
15 X 15	381 X 381	1	5.3	2.40
18 X 18	457 X 457	1	7.3	3.31
24 X 24	610 X 610	2	11.8	5.35

Wall or ceiling opening is $W + 3/8"$ (9 mm)
For detailed specifications see submittal sheet

