

# ACD-2064

## SPECIALTY DOORS

### Recessed Acoustical Access Door for Drywall

Highest STC & OITC Rating in the INDUSTRY

#### Application

This recessed access door is ideal for use on Acoustical drywall walls and ceilings where maintaining STC (Sound Transmission Class) and OITC (Outdoor-Indoor Transmission Class) is required. The unique taping bead flange allows for a concealed finish.

#### Product Features

- Zinc coated steel provides superior corrosion resistance
- Drywall taping bead flange
- Recessed door fitted with 5/8" thick drywall, ensures finish similar to surrounding
- Tested and evaluated to ASTM: E90(09), ASTM: E413(16), ASTM: E1332(16) and certified to STC Rating 64 and OITC Rating 53

#### ACD-2064 Specifications:

**Material:** 18 Gauge Satin Coat Steel

**Door:** 18 Gauge recessed design filled with 1½" thick acoustic mineral liner, 0.11" thick mineral filled vinyl barrier and fitted with 5/8" thick drywall as finished face

**Frame:** 18 Gauge, press bent for strength and rigidity, drywall taping bead flange  
Insulated with 1" thick acoustical mineral liner

**Gasket:** 1/8" x ½" Neoprene Rubber with Adhesive.

**Hinge:** Continuous exposed stainless steel piano hinge

**Standard Lock:** Slotted Screwdriver Cam Latch

**Optional Lock:** Compression Latch with Hex Head, Hex with security pin,  
Square, Triangle, Torx head with security pin

**Acoustic Rating:** This door has been tested and evaluated to ASTM: E90(09), ASTM: E413(16), ASTM: E1332(16) and certified to STC Rating 64 and OITC Rating 53.

**Finish:** Satin Coat Steel



#### ACD-2064 STANDARD SIZES

Nominal Door Size W&H		Latches	Weight per Door	
Inches	mm		lbs.	kg.
12 x 12	305 x 305	1	14.0	6.4
16 x 16	400 x 400	1	22.0	10.0
18 x 18	457 x 457	1	25.0	11.3
24 x 24	610 x 610	1	38.0	17.2
24 x 36	610 x 914	2	60.0	27.2

